

#30VTS

ventus VVS/S-type

WING
Fan Coil Unit

2019







01 VTS Group

1.1.	VTS Group	06
1.2.	3 pillars of success	08



02 Support for designers

2.1.	ClimaCad Online 4.0	12
2.2.	VTS BIM	14



03 VENTUS VVS Air Handling Units

3.1.	General specification	18
3.2.	Technical specification.....	26
3.2.1.	VVS 021-120 - Recuperator - cross-flow plate exchanger	26
3.2.2.	VVS 150-650 - Recuperator - cross-flow plate exchanger	28
3.2.3.	VVS 021-120 - Regenerator (rotary heat wheel).....	30
3.2.4.	VVS 150-650 - Regenerator (rotary heat wheel).....	32
3.2.5.	VVS 21-120 - Supply & Exhaust.....	34
3.2.6.	VVS 150-650 - Supply & Exhaust.....	36
3.2.6.	Additional configuration functions - VVS 021-650 - recuperator (hex & premium plus), regenerator (rotary heat wheel), supply & exhaust.....	38
3.3.	Components	40
3.4.	Controls.....	48
3.4.1.	Description.....	48
3.4.2.	Control elements	52



04 VENTUS S-type Air Handling Units

4.1.	Technical specification.....	60
------	------------------------------	----



05 Fan Coil Unit

5.1.	Technical specification.....	66
------	------------------------------	----




06 WING units

6.1.	WING	72
------	------------	----



07 Psychrometric chart (Mollier)

7.1.	Psychrometric chart [Mollier].....	77
------	------------------------------------	----





01

VTs Group



VTS GROUP – is a manufacturer of technically advanced HVAC equipment, combining innovative technologies in the field of research&development, production and logistics.




SHORTEST
L E A D
TIME ON THE MARKET *

* Logistics center



OUR MISSION

AHU#1





3 PILLARS OF SUCCESS

Constantly highest quality of products. Best prices on the market. Shortest lead time. These 3 pillars of marketing policy allows VTS to be always one step head, wherever in the world.

Following the best practices of the branch, VTS has created a network of 6 efficiently running production and logistic centers (**Atlanta, Dubai, Moscow, Shanghai, Warsaw, Bangalore**), enable to ensure the shortest lead time on the market, wherever in the world.

Large-scale production of repetitive units allow VTS to offer them at **the most competitive price, simultaneously keeping their highest possible quality**

Multistage quality control system allows VTS to offer **2 years warranty, extendable even up to 5.**

SHORTEST
LEAD
TIME ON THE MARKET


6 CENTERS
LOGISTIC


\$ COMPETITIVE
PRICE

110 000
UNITS
SOLD ANNUALLY

Q BEST
QUALITY

UP TO **5** YEARS WARRANTY
FOR EACH
UNIT







02

Support
for designers



CLIMACAD ONLINE 4.0 [CCOL 4]

Infinite number
of configurations

Friendly
user interface



Simple
and easy selection

Integration with CRM,
ERP & WMA systems

Certified by



CCOL4 OPTIMIZED FOR

» any
web-browser




» any operating system



» any device



DATA EXPORT TO






CCOL 4.0 utilises latest technologies and software platforms. The tool has been developed in SaaS model (Software as a Service). It's best advantage is, that service is accessible wherever in the world. Any device equipped with web-browser and internet access is all you need to experience the power of our CCOL 4.0.


DESIGN VERSATILITY

- » Infinite units configurations.
- » Detecting of configurations errors.




DYNAMIC AHU LENGTH DEFINITION

- » CCOL4 applies dynamic optimizing of AHU length based on automatic air treatment functions. placements with regard to minimum gaps between them in order to secure their proper performance.



MANAGING OF YOUR DATA BASE

- » Self-creating and development by designer of own projects and AHU selections data base.
- » Sharing of self-made AHU selections with VTS engineers for pricing.





VTs **BIM** - new approach to digital models of Air Handling Units

VTs has enabled dynamic generating of VENTUS VVS, VENTUS Compact and American VENTUS AVS units digital models as on-line service. This became possible thanks to implementation of new AHU selection tool – the ClimaCAD OnLine 4.0 [CCOL 4.0], equipped with .rfa [Revit®] files generator.




3 steps to generate the model:



1 Login to CCOL 4.0


You can login using our web-site:

www.ccol4.com




2 AHU configuration and parameters specifying

Intuitive unit configurator enables to select a unit, perfectly fitting to your design assumptions.






3 Selection export to .rfa file

In order to generate .rfa model, all you need to do is to enter personal information (including e-mail address) of a person to whom the model is to be sent. The system will automatically send the link to the site from where model can be downloaded. Entire process take no longer than 15 minutes.



The Autodesk REVIT® families shared by VTS significantly facilitate entire building modelling process done by designing bureaus. At the moment, the generator is an unique tool in entire BIM environment. It enables to generate brand new VENTUS units model on the spot, in any configuration or any parameters.

As a result the client is given:



Digital model of the air handling unit with fully parametrized connectors:

- » Air,
- » Hydraulic,
- » Sanitary,
- » Electric,

and also a set of complete technical and dimensioning information, including clearly marked **maintenance** and **service zone** of the unit.

VTS enables also a library of static families for WING air curtains and VOLCANO air heaters.

The models includes:

- » parametrized electric and hydraulic connectors,
- » both vertical and horizontal mounting options,
- » presentation of units effective air range,
- » parametrized angle of heater's to the horizontal plane.



VT**S BIM** -air handling units perfectly fitted for designer's needs.


VT**S** supports generating of air handling units models in LOD 400

(Level Of Development) standard.

In 2019, ClimaCAD OnLine 4.0 will support customization of the model's Level of Development, at the moment of their generating.

This will make the designing process even more flexible, especially when making first approaches to general concept of the building HVAC installations.

LOD
400
as standard






The VENTUS BIM families include maintenance and service zones of the units as standard.

These zones reserve minimum space to secure proper maintenance and repair conditions of the unit, and allow to avoid any collisions with remaining building elements or installations.

Service clearance **repair & maintenance** as standard.







03

Units
- VENTUS VVS

ventus

VVS



DURABLE
AND TIGHT
STRUCTURE



RELIABLE
COMPONENTS



Airflow

from **1 100** m³/h
from **100 000** m³/h



Up to **87%**
of energy recovery
efficiency



14
sizes




SMART
CONTROLS



USER
SAFETY



STRUCTURE



Z PROFILE

VS 21-150



C PROFILE

VS 180-650

GALVANIZED STEEL SUPPORT
AS **STANDARD** FOR ALL TYPES
OF UNITS

FRAME

- » easier transport
- » greater profile resistance to deflection



ALUMINIUM COLUMNS
AS **STANDARD**
FOR ALL TYPES
OF UNITS

FAN SECTION CAGE

- » increased longitudinal stiffness of the structure
- » easier sections assembly

STRUCTURAL COLUMNS

- » thermal breaks on the mullion as standard
- » high resistance to weather conditions and UV rays



TIGHTNESS





CANOPY

- » The canopy is made of 0,5 mm steel sheet, double side coated with 185 um of zinc (DX51D AZ185).
- » Canopy is assembled of modules equipped with self-latching grooves securing perfect tightness of the joints. Modular structure of the canopy ensures its easy and safe assembly.




ERGONOMIC INSPECTION PANEL LOCK


- » Highly aesthetic and ergonomic handles securing perfect tightness of inspection panels.



**THERMAL
BREAK**



**LABYRINTH
TIGHTENING**



**ADDITIONAL
POST SEALING**



**ADDITIONAL
SEALING BLADE**

ALUMINUM STRUCTURAL POSTS WITH ADDITIONAL SEALING BLADE AND THERMAL BREAK



- » Broken thermal bridge as standard – eliminates humidity condensation on units structural elements.
- » Blade along the inspection window ensures labyrinth tightening between panel and AHU body – currently the most effective solution on the market, mainly applied to laboratory equipment.
- » Symmetrical groove in the vertical post's mounting feet secures its 100% tightness with the AHU casing structure.



VVS 021-120 – RECUPERATOR - CROSS-FLOW PLATE EXCHANGERS

Nominal parameters			Recommended airflow range																						
Unit size		VVS021			VVS030			VVS040			VVS055			VVS075			VVS100			VVS120					
18 000 12 000 6 000 0	[m³/h]																								
		Min airflow																							
		Max airflow																							
		806	806	806	1 180	1 180	1 180	1 958	1 958	1 958	2 878	2 878	2 878	3 805	3 805	3 805	4 863	4 863	4 863	5 815	5 815	5 815			
		2 730	2 184	2 163	3 900	3 120	3 090	5 200	4 160	4 120	7 150	5 720	5 665	9 750	7 800	7 725	13 000	10 400	10 300	15 600	12 480	12 360			
H _{fd}		90			90			90			90			90			90			90					
H _{fU}		-			-			-			-			-			-			-					
H		538			670			670			805			925			1 025			1 062					
W		961			961			1 168			1 339			1 480			1 660			1 891					
H _i		368			500			500			635			755			855			892					
W _i		881			881			1 088			1 259			1 400			1 580			1 811					
H ₂		986			1 250			1 250			1 520			1 760			1 960			2 034					
I		40			40			40			40			40			40			40					

Selected configurations		Dimension		Length of selected configurations						
	FPDV/FVPD_cd	L2	[mm]	2221	2221	2221	2953	2953	3318	3318
		L1		2221	2221	2221	2953	2953	3318	3318
		K		-	-	-	-	-	-	-
		Lt		2221	2221	2221	2953	2953	3318	3318
	FPDV/FVPD_pd	L2	[mm]	2221	2221	2221	2953	2953	3318	3318
		L1		2221	2221	2221	2953	2953	3318	3318
		K		-	-	-	-	-	-	-
		Lt		2221	2221	2221	2953	2953	3318	3318
	FPDCV/FVPCD	L2	[mm]	2221	2221	2221	2953	2953	3318	3318
		L1		2587	2587	2587	3318	3318	3684	3684
		K		-	-	-	-	-	-	-
		Lt		2587	2587	2587	3318	3318	3684	3684
	FPDMCV/FVMPD	L2	[mm]	3318	3318	3318	4050	4050	4415	4415
		L1		3318	3318	3318	4050	4050	4415	4415
		K		-	-	-	-	-	-	-
		Lt		3318	3318	3318	4050	4050	4415	4415
	FPDMCVH/FVMPDH	L2	[mm]	3684	3684	3684	4415	4415	4781	4781
		L1		3318	3318	3318	4050	4050	4415	4415
		K		366	366	366	365	365	366	366
		Lt		3684	3684	3684	4415	4415	4781	4781

Entire range of configuration in ClimaCAD OnLine 4 selection tool - www.ccol4.com



DIMENSIONS - VVS021-VVS120 – RECUPERATOR - CROSS-FLOW PLATE EXCHANGERS

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	119		
VVS030	700	210	130	185		
VVS040	600	310	284	135		
VVS055	850	310	244	202		
VVS075	900	400	290	217		
VVS100	1200	400	230	267		
VVS120	1400	400	245	286		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	120		
VVS030	700	210	130	120		
VVS040	600	310	284	120		
VVS055	850	310	244	120		
VVS075	900	400	290	120		
VVS100	1200	400	230	120		
VVS120	1400	400	245	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS021	112	150	120	149		
VVS030	112	200	120	190		
VVS040	112	250	120	165		
VVS055	112	350	120	182		
VVS075	112	500	120	167		
VVS100	210	350	120	292		
VVS120	210	400	120	286		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
VVS100	1200	400	230	267	
VVS120	1400	400	245	286	

DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	84	
VVS030	256	256	352	142	
VVS040	288	288	441	92	
VVS055	408	408	340	84	
VVS075	452	452	420	94	
VVS100	510	510	480	112	
VVS120	572	572	480	88	

Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
VVS100	1200	400	230	267	
VVS120	1400	400	245	286	



DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	307	
VVS030	256	256	352	322	
VVS040	288	288	441	336	
VVS055	408	408	340	390	
VVS075	452	452	420	390	
VVS100	510	510	480	420	
VVS120	572	572	480	480	



VVS 150-650 – RECUPERATOR - CROSS-FLOW PLATE EXCHANGERS

Nominal parameters			Recommended airflow range																				
Unit size		VVS150			VVS180			VVS230			VVS300			VVS400			VVS500			VVS650			
90 000 60 000 30 000 0	[m³/h]																						
		+	x	-	+	x	-	+	x	-	+	x	-	+	x	-	+	x	-	+	x	-	
		7 167	7 167	7 167	8 640	8 640	8 640	10 398	10 398	10 398	13 491	13 491	13 491	18 704	18 704	18 704	21 817	21 817	21 817	28 725	28 725	28 725	
		19 500	15 600	15 450	23 400	18 720	18 540	29 900	23 920	23 690	39 000	31 200	30 900	52 000	41 600	41 200	71 500	57 200	56 650	84 500	67 600	66 950	
Min airflow																							
Max airflow																							
H _{fd}		90			120			120			120			120			120			120			
H _{fu}		0			80			80			80			80			80			80			
H		1 163			1 397			1 397			1 696			1 929			1 929			2 406			
W		2 085			2 085			2 493			2 585			3 085			3 585			3 697			
H _i		993			1 197			1 197			1 496			1 729			1 729			2 206			
W _i		2 005			2 005			2 413			2 505			3 005			3 505			3 617			
H ₂		2 236			2 754			2 754			3 352			3 818			3 818			4 772			
I		40			40			40			40			40			40			40			

Selected configurations			Length of selected configurations						
	L2	[mm]	3684	3684	3684	4781	4781	4781	5513
	L1		3684	3684	3684	4781	4781	4781	5513
	K		-	-	-	-	-	-	-
	Lt		3684	3684	3684	4781	4781	4781	5513
	L2	[mm]	3684	3684	3684	4781	4781	4781	5513
	L1		3684	3684	3684	4781	4781	4781	5513
	K		-	-	-	-	-	-	-
	Lt		3684	3684	3684	4781	4781	4781	5513
	L2	[mm]	3684	3684	3684	4781	4781	4781	5513
	L1		4050	4050	4050	5147	5147	5147	5878
	K		-	-	-	-	-	-	-
	Lt		4050	4050	4050	5147	5147	5147	5878
	L2	[mm]	5147	5147	5147	6244	6244	6244	6975
	L1		5147	5147	5147	6244	6244	6244	6975
	K		-	-	-	-	-	-	-
	Lt		5147	5147	5147	6244	6244	6244	6975
	L2	[mm]	5513	5513	5513	6610	6610	6610	7341
	L1		5513	5513	5513	6610	6610	6610	7341
	K		366	366	366	366	366	366	366
	Lt		5513	5513	5513	6610	6610	6610	7341

Entire range of configuration in ClimaCAD OnLine 4 selection tool - www.ccol4.com



DIMENSIONS - VVS150-VVS650 – RECUPERATOR - CROSS-FLOW PLATE EXCHANGERS

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	286		
VVS180	1700	500	192	388		
VVS230	1800	600	346	338		
VVS300	2060	700	262	438		
VVS400	2760	700	162	554		
VVS500	3060	800	262	504		
VVS650	3360	900	168	693		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	120		
VVS180	1700	500	192	120		
VVS230	1800	600	346	120		
VVS300	2060	700	262	120		
VVS400	2760	700	162	120		
VVS500	3060	800	262	120		
VVS650	3360	900	168	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS150	210	500	120	286		
VVS180	210	600	120	338		
VVS230	310	550	120	363		
VVS300	310	700	120	438		
VVS400	310	900	120	454		
VVS500	400	900	120	454		
VVS650	400	1150	120	568		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	500	210	230	119	
VVS180	700	210	130	185	
VVS230	600	310	284	135	
VVS300	850	310	244	202	
VVS400	900	400	290	217	
VVS500	1200	400	230	267	
VVS650	1400	400	245	286	

DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	98	
VVS180	718	718	480	162	
VVS230	804	804	770	112	
VVS300	902	902	740	172	
VVS400	1010	1010	1040	470	
VVS500	1134	1134	1230	102	
VVS650	1270	1270	1215	180	



Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS150	1400	500	342	286	
VVS180	1700	500	192	388	
VVS230	1800	600	346	338	
VVS300	2060	700	262	438	
VVS400	2760	700	162	554	
VVS500	3060	800	262	504	
VVS650	3360	900	168	693	



DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	510	
VVS180	718	718	480	520	
VVS230	804	804	770	600	
VVS300	902	902	740	600	
VVS400	1010	1010	1040	640	
VVS500	1134	1134	1230	700	
VVS650	1270	1270	1215	720	



VVS 021-120 - ROTARY HEAT WHEEL

Nominal parameters			Recommended airflow range																							
Unit size		VVS021			VVS030			VVS040			VVS055			VVS075			VVS100			VVS120						
18 000 12 000 6 000 0	[m³/h]																									
		Min airflow	806	806	806	1 180	1 180	1 180	1 958	1 958	1 958	2 878	2 878	2 878	3 805	3 805	3 805	4 863	4 863	4 863	5 815	5 815	5 815			
		Max airflow	2 730	2 415	2 163	3 900	3 450	3 090	5 200	4 600	4 120	7 150	6 325	5 665	9 750	8 625	7 725	13 000	11 500	10 300	15 600	13 800	12 360			
H _{fd}		90			90			90			90			90			90			90						
H _{fu}		0			0			0			0			0			0			0						
H		538			670			670			805			925			1 025			1 062						
W		961			961			1 168			1 339			1 480			1 660			1 891						
H _i		368			500			500			635			755			855			892						
W _i		881			881			1 088			1 259			1 400			1 580			1 811						
H ₂		986			1 250			1 250			1 520			1 760			1 960			2 034						
I		40			40			40			40			40			40			40						

Selected configurations			Length of selected configurations						
	L2	[mm]	1 830	1 830	1 830	2 196	2 196	2 562	2 562
			L1	1 830	1 830	1 830	2 196	2 196	2 562
			K	366	366	366	732	732	1 098
			Lt	1 830	1 830	1 830	2 196	2 196	2 562
	L2	[mm]	2 562	2 562	2 562	2 928	2 928	3 294	3 294
			L1	2 562	2 562	2 562	2 928	2 928	3 294
			K	366	366	366	366	366	366
			Lt	2 562	2 562	2 562	2 928	2 928	3 294
	L2	[mm]	1 830	1 830	1 830	2 196	2 196	2 562	2 562
			L1	2 196	2 196	2 196	2 562	2 562	2 928
			K	366	366	366	732	732	1 098
			Lt	2 196	2 196	2 196	2 562	2 562	2 928
	L2	[mm]	2 562	2 562	2 562	2 928	2 928	3 294	3 294
			L1	2 928	2 928	2 928	3 294	3 294	3 660
			K	0	0	0	0	0	0
			Lt	2 928	2 928	2 928	3 294	3 294	3 660
	L2	[mm]	1 830	1 830	1 830	2 196	2 196	2 562	2 562
			L1	2 196	2 196	2 196	2 562	2 562	2 928
			K	366	366	366	732	732	1 098
			Lt	2 196	2 196	2 196	2 562	2 562	2 928
	L2	[mm]	2 562	2 562	2 562	2 928	2 928	3 294	3 294
			L1	2 928	2 928	2 928	3 294	3 294	3 660
			K	0	0	0	0	0	0
			Lt	2 928	2 928	2 928	3 294	3 294	3 660
	L2	[mm]	3 378	3 378	3 378	3 744	3 744	4 110	4 110
			L1	4 138	4 138	4 138	4 504	4 504	4 870
			K	366	366	366		366	366
			Lt	4 138	4 138	4 138	4 504	4 504	5 236

Entire range of configuration in ClimaCAD OnLine 4 selection tool - www.ccol4.com



DIMENSIONS - VVS021-VVS120 - ROTARY HEAT WHEEL

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	119		
VVS030	700	210	130	185		
VVS040	600	310	284	135		
VVS055	850	310	244	202		
VVS075	900	400	290	217		
VVS100	1200	400	230	267		
VVS120	1400	400	245	286		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	120		
VVS030	700	210	130	120		
VVS040	600	310	284	120		
VVS055	850	310	244	120		
VVS075	900	400	290	120		
VVS100	1200	400	230	120		
VVS120	1400	400	245	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS021	112	150	120	149		
VVS030	112	200	120	190		
VVS040	112	250	120	165		
VVS055	112	350	120	182		
VVS075	112	500	120	167		
VVS100	210	350	120	292		
VVS120	210	400	120	286		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
VVS100	1200	400	230	267	
VVS120	1400	400	245	286	

DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	84	
VVS030	256	256	352	142	
VVS040	288	288	441	92	
VVS055	408	408	340	84	
VVS075	452	452	420	94	
VVS100	510	510	480	112	
VVS120	572	572	480	88	

Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
VVS100	1200	400	230	267	
VVS120	1400	400	245	286	

DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	307	
VVS030	256	256	352	322	
VVS040	288	288	441	336	
VVS055	408	408	340	390	
VVS075	452	452	420	390	
VVS100	510	510	480	420	
VVS120	572	572	480	480	



VVS 150-650- ROTARY HEAT WHEEL

Nominal parameters			Recommended airflow range																							
Unit size			VVS150			VVS180			VVS230			VVS300			VVS400			VVS500			VVS650					
90 000 60 000 30 000 0	[m³/h]	</																								



DIMENSIONS - VVS150-VVS650 - ROTARY HEAT WHEEL

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	286		
VVS180	1700	500	192	388		
VVS230	1800	600	346	338		
VVS300	2060	700	262	438		
VVS400	2760	700	162	554		
VVS500	3060	800	262	504		
VVS650	3360	900	168	693		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	120		
VVS180	1700	500	192	120		
VVS230	1800	600	346	120		
VVS300	2060	700	262	120		
VVS400	2760	700	162	120		
VVS500	3060	800	262	120		
VVS650	3360	900	168	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS150	210	500	120	286		
VVS180	210	600	120	338		
VVS230	310	550	120	363		
VVS300	310	700	120	438		
VVS400	310	900	120	454		
VVS500	400	900	120	454		
VVS650	400	1150	120	568		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	500	210	230	119	
VVS180	700	210	130	185	
VVS230	600	310	284	135	
VVS300	850	310	244	202	
VVS400	900	400	290	217	
VVS500	1200	400	230	267	
VVS650	1400	400	245	286	





DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	98	
VVS180	718	718	480	162	
VVS230	804	804	770	112	
VVS300	902	902	740	172	
VVS400	1010	1010	1040	470	
VVS500	1134	1134	1230	102	
VVS650	1270	1270	1215	180	


Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS150	1400	500	342	286	
VVS180	1700	500	192	388	
VVS230	1800	600	346	338	
VVS300	2060	700	262	438	
VVS400	2760	700	162	554	
VVS500	3060	800	262	504	
VVS650	3360	900	168	693	

DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	510	
VVS180	718	718	480	520	
VVS230	804	804	770	600	
VVS300	902	902	740	600	
VVS400	1010	1010	1040	640	
VVS500	1134	1134	1230	700	
VVS650	1270	1270	1215	720	





VVS021-VVS150 - SUPPLY & EXHAUST

Nominal parameters					Recommended airflow range																											
Unit size		VVS021				VVS030				VVS040				VVS055				VVS075				VVS100				VVS120						
20 000 15 000 10 000 5 000 0	[m³/h]																															
		⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙	⊖	⊕	⊗	⊙			
		806	806	806	806	1180	1180	1167	1167	1958	1958	1958	1958	2878	2878	2878	2878	3805	3805	3805	3805	4863	4863	4863	4863	5815	5815	5815	5815			
		2163	2730	3570	3780	3090	3900	5100	5400	4120	5200	6800	7200	5665	7150	9350	9900	7725	9750	12750	13500	10300	13000	17000	18000	12360	15600	20400	21600			
		Min airflow	806	806	806	806	1180	1180	1167	1167	1958	1958	1958	1958	2878	2878	2878	2878	3805	3805	3805	3805	4863	4863	4863	4863	5815	5815	5815	5815		
Max airflow	2163	2730	3570	3780	3090	3900	5100	5400	4120	5200	6800	7200	5665	7150	9350	9900	7725	9750	12750	13500	10300	13000	17000	18000	12360	15600	20400	21600				
H _{fd}	[mm]	90				90				90				90				90				90				90						
H		538				670				670				805				925				1 025				1 062						
W		961				961				1 168				1 339				1 480				1 660				1 891						
H _i		368				500				500				635				755				855				892						
W _i		881				881				1 088				1 259				1 400				1 580				1 811						
I		40				40				40				40				40				40				40						

Selected configurations		Dimension	Length of selected configurations						
	F-CV	Lt	1181*	1181*	1181*	1547	1547	1913	1913
	MFCV	Lt	1490*	1490*	1490*	1856	2221	2587	2587
	FCV	Lt	1572*	1572*	1572*	1938	1938	2303	2303
	MFFCV	Lt	2221*	2221*	2221*	2587	2587	2953	2953
	FV	Lt	1098	1098	1098	1464	1464	1830	1830
	V	Lt	732	732	732	1098	1098	1464	1464

Entire range of configuration in ClimaCAD OnLine 4 selection tool - www.ccol4.com



General:

* If 8RD with eliminator, length will increase by 366mm

** If RA is required on top, length will increase by 366mm



DIMENSIONS - VVS021-VVS120 - SUPPLY & EXHAUST

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	119		
VVS030	700	210	130	185		
VVS040	600	310	284	135		
VVS055	850	310	244	202		
VVS075	900	400	290	217		
SSV100	1200	400	230	267		
VVS120	1400	400	245	286		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS021	500	210	230	120		
VVS030	700	210	130	120		
VVS040	600	310	284	120		
VVS055	850	310	244	120		
VVS075	900	400	290	120		
SSV100	1200	400	230	120		
VVS120	1400	400	245	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS021	112	150	120	149		
VVS030	112	200	120	190		
VVS040	112	250	120	165		
VVS055	112	350	120	182		
VVS075	112	500	120	167		
SSV100	210	350	120	292		
VVS120	210	400	120	286		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
SSV100	1200	400	230	267	
VVS120	1400	400	245	286	








DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	84	
VVS030	256	256	352	142	
VVS040	288	288	441	92	
VVS055	408	408	340	84	
VVS075	452	452	420	94	
SSV100	510	510	480	112	
VVS120	572	572	480	88	

Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS021	500	210	230	119	
VVS030	700	210	130	185	
VVS040	600	310	284	135	
VVS055	850	310	244	202	
VVS075	900	400	290	217	
SSV100	1200	400	230	267	
VVS120	1400	400	245	286	

DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS021	206	206	377	307	
VVS030	256	256	352	322	
VVS040	288	288	441	336	
VVS055	408	408	340	390	
VVS075	452	452	420	390	
SSV100	510	510	480	420	
VVS120	572	572	480	480	





VVS 150-650 - SUPPLY & EXHAUST

Nominal parameters		Recommended airflow range																											
Unit size		VVS150				VVS180				VVS230				VVS300				VVS400				VVS500				VVS650			
120 000 90 000 60 000 30 000 0	[m³/h]																												
		⊖ ⊕ ⊗ ⊙				⊖ ⊕ ⊗ ⊙				⊖ ⊕ ⊗ ⊙				⊖ ⊕ ⊗ ⊙				⊖ ⊕ ⊗ ⊙				⊖ ⊕ ⊗ ⊙							
		7 167 7 167 7 167 7 167				8 640 8 640 8 640 8 640				10 398 10 398 10 398 10 398				13 491 13 491 13 491 13 491				18 704 18 704 18 704 18 704				21 817 21 817 21 817 21 817				28 725 28 725 28 725 28 725			
		15 450 19 500 25 500 27 000				18 540 23 400 30 600 32 400				23 690 29 900 39 100 41 400				30 900 39 000 51 000 54 000				41 200 52 000 58 000 62 000				56 650 71 500 77 000 79 000				66 950 84 500 87 000 100 000			
Min airflow		7 167 7 167 7 167 7 167				8 640 8 640 8 640 8 640				10 398 10 398 10 398 10 398				13 491 13 491 13 491 13 491				18 704 18 704 18 704 18 704				21 817 21 817 21 817 21 817				28 725 28 725 28 725 28 725			
Max airflow		15 450 19 500 25 500 27 000				18 540 23 400 30 600 32 400				23 690 29 900 39 100 41 400				30 900 39 000 51 000 54 000				41 200 52 000 58 000 62 000				56 650 71 500 77 000 79 000				66 950 84 500 87 000 100 000			
H _{fd}		90				120				120				120				120				120				120			
H _{fu}		0				80				80				80				80				80				80			
H		1 163				1 397				1 397				1 696				1 929				1 929				2 406			
W		2 085				2 085				2 493				2 585				3 085				3 585				3 697			
H _i		993				1 197				1 197				1 496				1 729				1 729				2 206			
W _i		2 005				2 005				2 413				2 505				3 005				3 505				3 617			
H ₂		2 236				2 754				2 754				3 352				3 818				3 818				4 772			
I		40				40				40				40				40				40				40			

Selected configurations		Dimension		Length of selected configurations							
	F-CV	[mm]	Lt	1913	1913	1913	2278	2278	2278	2278	2278
	MFCV		Lt	2587	2587	2587	2953	2953	2953**	2953**	2953**
	FCV		Lt	2303	2303	2303	2669	2669	2669	2669	2669
	MFFCV		Lt	2953	2953	2953	3318	3318	3318**	3318**	3318**
	FV		Lt	1830	1830	1830	2196	2196	2196	2196	2196
	V		Lt	1464	1464	1464	1830	1830	1830	1830	1830

Entire range of configuration in ClimaCAD OnLine 4 selection tool - www.ccol4.com



General:

* If 8RD with eliminator, length will increase by 366mm

** If RA is required on top, length will increase by 366mm



DIMENSIONS - VVS021-VVS120 - SUPPLY & EXHAUST

Opening BIG - inlet-outlet END (FF)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	286		
VVS180	1700	500	192	388		
VVS230	1800	600	346	338		
VVS300	2060	700	262	438		
VVS400	2760	700	162	554		
VVS500	3060	800	262	504		
VVS650	3360	900	168	693		

Opening BIG - inlet-outlet END (US)						
Size	WA	HA	WA1	HA1		
VVS150	1400	500	342	120		
VVS180	1700	500	192	120		
VVS230	1800	600	346	120		
VVS300	2060	700	262	120		
VVS400	2760	700	162	120		
VVS500	3060	800	262	120		
VVS650	3360	900	168	120		

Opening BIG - inlet-outlet END (BS)						
Size	WA	HA	WA1	HA1		
VVS150	210	500	120	286		
VVS180	210	600	120	338		
VVS230	310	550	120	363		
VVS300	310	700	120	438		
VVS400	310	900	120	454		
VVS500	400	900	120	454		
VVS650	400	1150	120	568		

FAN OUTLET OPENINGS

Plug Fan END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	500	210	230	119	
VVS180	700	210	130	185	
VVS230	600	310	284	135	
VVS300	850	310	244	202	
VVS400	900	400	290	217	
VVS500	1200	400	230	267	
VVS650	1400	400	245	286	

DIDW END (FS)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	98	
VVS180	718	718	480	162	
VVS230	804	804	770	112	
VVS300	902	902	740	172	
VVS400	1010	1010	1040	470	
VVS500	1134	1134	1230	102	
VVS650	1270	1270	1215	180	

Plug Fan END (US)					
Size	WA	HA	WA1	HA1	
VVS150	1400	500	342	286	
VVS180	1700	500	192	388	
VVS230	1800	600	346	338	
VVS300	2060	700	262	438	
VVS400	2760	700	162	554	
VVS500	3060	800	262	504	
VVS650	3360	900	168	693	


DIDW END (US)					
Size	WA	HA	WA1	HA1	
VVS150	642	642	610	510	
VVS180	718	718	480	520	
VVS230	804	804	770	600	
VVS300	902	902	740	600	
VVS400	1010	1010	1040	640	
VVS500	1134	1134	1230	700	
VVS650	1270	1270	1215	720	



ADDITIONAL CONFIGURATION FUNCTIONS - VVS 021-650 - RECUPERATOR (HEX & PREMIUM PLUS), REGENERATOR (HEAT WHEEL), SUPPLY & EXHAUST

Dimension			Function version	Remaining configuration functions – typical lengths of function arrangement						
				VVS021	VVS030	VVS040	VVS055	VVS075	VVS100	VVS120
 F	L	[mm]	F7/F9	762	762	762	762	762	762	762
			EU4/F5	366	366	366	366	366	366	366
 H	L		H	366	366	366	366	366	366	366
 C	L		C	366	366	366	366	366	366	366
 S	L		S	1098	1098	1098	1098	1098	1098	1098
 E	L		E(e1)	366	366	366	366	366	366	366
			E(e2)	762	762	762	762	762	762	762
			E(e3)	1098	1098	1098	1098	1098	1098	1098
 M	L		M	762	762	762	762	762	762	762
 W	L		W	1098	1098	1098	1098	1098	1098	1098

Dimension		Function version		Remaining configuration functions – typical lengths of function arrangement							
				VVS150	VVS180	VVS230	VVS300	VVS400	VVS500	VVS650	
 F	L	[mm]	F7/F9	762	762	762	762	762	762	762	
			EU4/F5	366	366	366	366	366	366	366	
 H	L		H	366	366	366	366	366	366	366	
			 C	L	C	366	366	366	366	366	366
 S	L				S	1098	1098	1098	1098	1098	1098
			 E	L	E(e1)	366	366	366	366	366	366
E(e2)	762				762	762	762	762	762	762	
E(e3)	1098				1098	1098	1098	1098	1098	1098	
 M	L		M	1098	1098	1098	1098	1098	1098	1098	1098
			 W	L	W	1098	1098	1098	1098	1098	1098



ventus

ventus



COMPONENTS

FAN SET

> DIRECT DRIVE PLUG FAN SET



Design and application

- » Single inlet, radial, backward curved, free running fan.
- » Impeller made of SAN (styrene/acrylonitrile) construction material with 20% glass fiber.
- » Direct drive – fan impeller installed directly on motor shaft.
- » Fan section consisting of single or multiple fans (fan array) in order to ensure optimum working parameters.

Specification

- » Low and medium pressure ventilation systems with fan static pressure not exceeding 2000 Pascals.
- » Maximum fan set working temperature: 60°C.
- » Compliance with standards: EN 1886, EN 25136, ISO 5801, AMCA standard 210.

> BELT DRIVE DIDW FAN SET



- » The DIDW centrifugal fans (Double Inlet Double Width Fans) are suitable for supply or extract applications in commercial, process and industrial HVAC systems.
- » Sizes are in accordance with AMCA standard 99-0098-76 R20.
- » The operating limit is design to meet the requirement of class I, II and III limit as defined in AMCA standard 99-2408-69.

Wheel

- » The wheels are available in options:
 - Forward curved blades,
 - Backward curved bladed (air foil or straight shape)
- » The impeller with forward curved blades is manufactured in galvanized sheet steel.
- » The impeller with backward inclined blades is made of cold rolled sheet steel backward curved blades with polyester powder coating finish.

Housing

- » For all sizes the housing is manufactured in galvanized sheet steel with the housing fixed to the side plates in "pittsburg lock" form system.

Frame

- » The frame is manufactured with galvanized angular bars or steel finished with polyester powder coating.

Shaft

- » Shafts are manufactured from C45 carbon steel coated with an anti-corrosion varnish after assembly.

Bearings

- » Bearings used are either deep groove ball bearing type with an eccentric locking collar or an adapter sleeve, or spherical roller bearings type sealed at both sides for different duty.

> AC MOTORS




- » Fan and motor mounted on common housing, separated from AHU casing by set of rubber vibration absorbing mounts.
- » Motors of TEFC type (Totally Enclosed, Fan-Cooled).
- » Motors fitted for IEC standard.
- » Variable Frequency Drive (VFD) – standard equipment of the fan-set.

- » Available Energy classes: IE2, IE3
- » Rated voltage: 3x230V AC, 3x400V AC.
- » Number of poles: 2 or 4.
- » Motor winding insulation class: F (fitted for VFD operations).
- » Bearings lifetime: $L_{10} = 20000h$ / $L_{50} = 100000h$.
- » Protection degree: IP55.
- » Maximum working ambient temperature: 60°C.



CASING



Design and application

- » Casing structure made of 'sandwich' type panels formed in 'C' shape and reinforced by system of internal frames.
- » "Sandwich" double skin panels made of rigid polyurethane foam.
- » Indoor and outdoor application.
- » Inspection panels mounted on AHU side.
- » Casing supported on steel base rails.



Specification

- » Working temperature: $(-40)^{\circ}\text{C} \div (+90)^{\circ}\text{C}$.
- » Panel thickness: 40mm.
- » Thermal conductivity PPU $\lambda = 0,022 \text{ W/mK}$.
- » Casing fire resistance: non-flamable, non fire spreading (NRO).
- » Moisture absorption: 0,04%.
- » PPU density: $\rho = 42 \text{ kg/m}^3$.
- » Eurovent certification
 - Mechanical strength of casing: $-1000 \text{ Pa} \div 1000 \text{ Pa} < 2 \text{ mm}$ (D_1 - PN EN 1886: 2008),
 - Casing tightness: (MB): $(-400) \text{ Pa} - 0,05 \text{ l/sm}^2$, $(+700) \text{ Pa} - 0,13 \text{ l/sm}^2$ (L_1 - PN EN 1886: 2008); (RU): $(+400) \text{ Pa} - 0,93 \text{ l/sm}^2$,
 - Casing heat transfer coefficient: $K = 0,6 \text{ W/m}^2\text{K}$ (T_2 - PN EN 1886: 2008),
 - Thermal bridges coefficient: $K_p = 0,69$ (TB_2 - PN EN 1886: 2008).

PANEL FILTERS



Design and application

- » Box Type
- » Pleated filtration fabric shielded by steel net, installed in 50 mm thick frame.
- » Filtration fabric made of polyester fibres.
- » Applied as initial air filtration stage.

Specification

- » Working temperature: max $(+70)^{\circ}\text{C}$, 100% RH.

Filtration classes available

- » ISO Coarse 75% (ISO 16890) - G4 (EN779).

BAG FILTERS



Design and application

- » Flange Type & Bag Type
- » Filtration fabric made of polyester fibres.
- » Bags fixed to 25 mm thick frame.
- » Length: 300/600 mm.
- » Applied as initial, secondary or final air filtration stage

Specification

- » Working temperature: max $(+70)^{\circ}\text{C}$, 100% RH.

Filtration classes available

- » ISO ePM10 50% (ISO 16890) - M5 (EN779).
- » ISO ePM2,5 65% (ISO 16890) - F7 (EN779).
- » ISO ePM1 70% (ISO 16890) - F9 (EN779).

HEPA FILTERS



Design and application

- » Flange Type & Box Type
- » Filter Media: Glass Fiber / Spun Bonded Polyester
- » Length 300/600 mm.
- » Applied as final air filtration stage
- » Frame Material: Aluminum (SS 304 / GI (Galvanized Steel))

Specification


- » Working temperature: max $(+70)^{\circ}\text{C}$, 100% RH.

Filtration classes available

- » H13 (EN 1822).
- » Filtration Rating: 0.3 Micron & More
- » Filtration Efficiency: 90- 99.9 %



ROTARY HEAT WHEEL



Design and application Non-hygroscopic

- » Rotor made of circular aluminum honeycomb matrix with shaft suspended on bearings, installed in steel housing.
- » Rotor filling – two layers of alternately winded aluminium foil – one flat, the other – corrugated – making small ducts for the air.
- » Rotor drive system with smooth revolutions control enabling to maintain highest recovery efficiency and to adjust degree of recovery performance.
- » Purge zone reducing the cross-contamination effect of contaminated exhaust air to supply to absolute minimum.
- » Set of gaskets installed both on the wheel outer edge and bar separating supply from exhaust air being an additional protection against cross-contamination.
- » Rotary heat wheel recovers sensible heat from return air to supply, which passes the unit in opposite direction. The process enables heat recovery in winter time, same as cool recovery in summer.
- » Bearings: Permanently sealed and lubricated ball bearings. Oversized bearings designed for over 200 000 hours of duty (20 000 L10 hours of duty).

- » Rotor filling – two layers of alternately winded aluminium foil – one flat, the other – corrugated – making small ducts for the air.
- » Rotor drive system with smooth revolutions control enabling to maintain highest recovery efficiency and to adjust degree of recovery performance.
- » Purge zone reducing the cross-contamination effect of contaminated exhaust air to supply to absolute minimum.
- » Set of gaskets installed both on the wheel outer edge and bar separating supply from exhaust air being an additional protection against cross-contamination.
- » Desiccant type: 3A molecular sieve as desiccant for fast absorption of moisture and antimicrobial properties
- » Rotary heat wheel recovers both sensible and latent heat from return air to supply, which passes the unit in opposite direction. The process enables heat recovery in winter time, same as cool recovery in summer.
- » Bearings: Permanently sealed and lubricated ball bearings. Oversized bearings designed for over 200 000 hours of duty (20 000 L10 hours of duty).

Total - sorption


- » Rotor made of circular aluminum honeycomb matrix with shaft suspended on bearings, installed in steel housing.
- » Rotor's aluminium with desiccant coating for latent recovery.

Specification

- » Up to 86% of energy recovery, depending on airflow rate and its velocity in the heat wheel window.
- » Compliance with standards: EN 308, EN 13053.

THE DOUBLE WHEEL CONCEPT


The double wheel system is one of the most effective systems for air dehumidifying with energy recovery. This concept perfectly combines energy recovery with dehumidification. This system uses both total-sorption thermal wheel and a non-hygroscopic thermal wheel with a cooling coil in between.



- » The Double Wheel Concept saves up to 60% of the total cooling capacity and requires lower investment and running costs compared to traditional systems. As rule of thumb, the additional cost of the sensible wheel can be saved in the lower investment compared to traditional system components, coils, chillers, cold and hot water piping installation, pumps, valves, controls and electric power supply costs. Accurate total investment costs analyze of the complete installation will show major savings in initial costs. Both cooling and heating energy savings will be additional profit of the investment



CROSSFLOW PLATE HEAT RECUPERATOR



Design and application

- » Recuperator made of crosswise stamped aluminum plates, between which supply and exhaust air passes alternately in counterflow arrangement.
- » As standard, the recuperator is equipped with by-pass damper, enabling its securing against frosting and heat recovery capacity regulation.
- » Optionally, the recuperator can be equipped with integrated mixing box.
- » The recuperator provides sensible heat recovery for warmer air to the colder one. For winter season – recovery of heat from return air to supply. For summer – recovery of chill from return air to supply.

Specification

- » Energy recovery at very high supply and exhaust air stream separation (reaching 99,9%)
- » Heat recovery reaching up to 80% depending on flow rate face velocity of the air passing the recuperator.
- » Compliance with standards: EN 308, EN 13053.
- »

RUN-AROUND COIL



Design and application

- » Set of two water coils – one in supply, the other one in exhaust airstream.
- » The coil in return airstream recovers the heat (cooler) and passes it to the coil in the supply air (heater) by means of heat-transfer fluid (water-glycol mixture). In case of chill recovery, entire process is reversed.
- » System applied for supply and exhaust air handling units installed remotely to each other."

Specification

- » Indirect Energy recovery (sensible heat) at 100% supply and exhaust airstreams separation.
- » Max heat-transfer fluid operation pressure: 1,6MPa=16bar (tested 21 bar).
- » Max glycol concentration: 50%.
- » Compliance with standards: EN 308, EN 13053.
- »

MIXING SECTION



Design and application

- » Section equipped with two air inlets/outlets aided with dampers, enabling regulation of fresh and recirculation air share (recirculation).

Specification

- » Direct Energy recovery (sensible and latent heat) resulting from partial mixing of fresh air with return one.
- » Control of fresh air share in entire airflow supplied to handled spaces.
- » Working temperature range: $-40 \div +70^{\circ}\text{C}$.



WATER HEATER



Design and application

- » Block of copper pipes integrated with another block of aluminum fins, creating expanded heat exchange surface. Pipes are bonded to the collectors, equipped with headers (for connecting entire coil to the medium supply system).
- » Heating of the air supplied to the handled spaces.
- » Re-heating of the air as a part of air dehumidifying process.
- » The coil can be applied if heating medium is available (local boiler or district heating system).
- » Coil headers are equipped with medium damping valve and air vent.
- » Connecting the coil in parallel medium flow vs air, will result in its capacity reduction by over a dozen percent.

Specification

- » Max glycol concentration: 50%.
- » Max medium temperature: 150°C.
- » Max medium working pressure: 1,6MPa = 16bar (test: 21bar).
- » Heating capacity: parameter resulting from individual performance calculation of selected unit (CCOL).
- » Medium side pressure drop – parameter resulting from individual performance calculation of selected unit (CCOL).
- » Compliance with standards: EN 305, EN 1216, EN 13053.

ELECTRIC HEATER




Design and application

- » Set of resistive heating elements made of CR-Ni-Fe alloy, 6 kW/400V each.
- » Coils mounted on hot-dip galvanized steel frame.
- » Heater is equipped with power terminals and thermostat protecting against overheating.
- » In case of AHU with complete controls, heater is equipped with integrated capacity control module.
- » Heating capacity can be modified by means of smooth regulation module (HE module, set of Solid State Relays as optional parts of AHU controls) or by means of automatic engaging of next heating sections.

Specification

- » Max permissible ambient temperature around heating elements: 65°C.

WRAP-AROUND HEAT PIPES



Design and application


- » Wrap around dehumidifier heat pipes are passive devices intended for use in air conditioning equipment to enhance dehumidification, reduce load on air conditioning equipment, and reduce or eliminate reheat.
- » The Wrap-Around Heat Pipe consists of: a pre-cool DX coil, a re-heat DX coil and heat pipes connecting the coils. The two heat pipe coils are designed to be installed around the existing cooling coil. Cooling coil can be either chilled water or DX.

Specification

- » Working medium: R134a
- » Tested for pressure: 1.3 MPa (13 Bar)
- » Fin thickness: 0,1mm
- » Row number: 1-3
- » FPI: 9-15
- » Compliance with standards: EN 305, EN 1216, EN 13053.



DIRECT EXPANSION COIL AS CONDENSER IN HEAT PUMP CIRCUIT



Design and application

- » Block of copper pipes integrated with another block of aluminum fins, creating expanded heat exchange surface. Pipes are bonded to the collectors, equipped with headers (for connecting entire coil to the cooling system circuit).
- » Heating of the air supplied to the handled spaces.
- » Re-heating of the air as a part of air dehumidifying process.

Specification

- » Max medium temperature: 60°C.
- » Max medium working pressure: 3,84MPa = 38,4bar (test: 50bar).
- » Heating capacity: parameter resulting from individual performance calculation of selected unit (CCOL).
- » Compliance with standards: EN 305, EN 1216, EN 13053.

WATER COOLER




Design and application

- » Block of copper pipes integrated with another block of aluminum fins, creating expanded heat exchange surface. Pipes are bonded to the collectors, equipped with headers (for connecting entire coil to the medium supply system).
- » Cooling of the air supplied to handled spaces.
- » Cooling and dehumidifying of the air as a part of air complex dehumidifying process in summer season.
- » Coil can be applied in complex air conditioning systems consisting of few or over a dozen of units supplied from common chilling source (chiller) or in case of single unit of relatively high cooling capacity.

Specification

- » Max glyccol concentration: 50%.
- » Min supplying medium temperature: +2°C.
- » max medium working pressure: 1,6MPa = 16bar (test: 21bar).
- » Cooling capacity: parameter resulting from individual parameters of selected unit (CCOL).
- » Medium pressure drop / flow rate: parameter resulting from individual performance calculation of selected unit (CCOL).
- » For reversed operation mode (heating) max medium working temperature: 140°C.
- » Compliance with standards: EN 305, EN 1216, EN 13053.

DX COOLING COIL



Design and application

- » Block of copper pipes integrated with another block of aluminum fins, creating expanded heat exchange surface. Pipes are bonded to the collectors, equipped with headers (for connecting entire coil to the cooling system circuit).
- » DX cooler is also available as heater execution (so called Condenser).
- » Cooling and dehumidifying of the air as a part of air complex dehumidifying process in summer season.
- » Coil usually applied for smaller cooling capacity systems vs water coolers or for individual air conditioning systems.

Specification

- » Min. Refrigerant evaporation temperature: +3°C.
- » Max refrigerant working pressure: 2,2MPa=22bar (test: 29 bar).
- » Cooling capacity - parameter resulting from individual performance calculation of selected unit (CCOL).
- » Compliance with standards: EN 305, EN 1216, EN 13053.



EVAPORATIVE HUMIDIFIER



Design and application

- » Humidifying process based on water adiabatic evaporation from the humidifier pad.
- » Humidifying pad made of CELDEK II material.
- » Humidifier housing made of stainless steel.
- » System of direct water dropping (VVS021-VVS055).
- » System of water recirculation aided by pump (VVS075-VVS650).
- » Droplet eliminator integrated with humidifier filling (VVS075-VVS650).
- » System is equipped with water drainage system preventing against high water level in the pan and floating valve controlling its refilling (VVS075-VVS 650).

Specification

- » Max air face velocity across the humidifier pad: 3,00 m/s (VS 21-VS 55); 4,00 m/s (VS 75-VS 650).
- » Water pressure range: 0,15 ÷ 0,75 MPa.
- » Requirements regarding water quality – standard tap water.

SOUND ATTENUATING SECTION



Design and application

- » Sound attenuator consists of noise attenuating bars installed in the AHU casing.
- » Attenuating bars of 140 mm width filled with sound-absorbing, inflammable mineral wool (density: 60 and 80 kg/m³).
- » Attenuating bar housing: frame made of hot-dip galvanized steel.
- » Bar outer surface: thin veil preventing against bar filling migration to the air.
- » Number of attenuating bars: 2÷13, depending on block size.

Specification

- » Max air face velocity: v=5m/s.
- » Working conditions: -40 ÷ +70°C.

INTERNAL LIGHT



Design and application

- » Energy saving lamp with securing shade.
- » Facilitation of AHU inspection actions: filter, fan and humidifier compartment.

Specification

- » Working conditions: -40 ÷ +70°C.



AIR DAMPER



Design and application

- » Blades made of aluminium with rubber gasket on the edges.
- » Aluminum frame.
- » Blades drive realized by means of gears made of composite material, installed on frame internal side.
- » Damper is equipped with square pivot, fitted for actuator (dampers of cross section greater than 4 m² have 2 linked pivots).

Specification

- » Air leakage at closed damper: 50 m³/h*m² - at 100 Pascals of pressure difference.
- » Working temperature range: -40 ÷ +70°C.

FLEXIBLE CONNECTION



Design and application

- » Flexible connection made of 1 mm thick and 30 mm wide hot-dip galvanized steel profiles and polyester fabric coated with PVC.
- » Flame resistance: UL94 - HB [ISO 1210].
- » Flexible connection resistant to UV radiation.
- » Working temperature range: -30°C do +70°C.
- » Max connection length (fully spread position): 110 mm.
- » Flexible connection installed on each AHU/Duct joint eliminates transfer of possible AHU vibrations to the ventilation ductwork.

Specification

- » Max air face velocity: 5m/s.
- » Working conditions: -40 ÷ +70°C.

AIR INTAKE AND DISCHARGE LOUVERS



Design and application

- » Air intake louver made of aluminum profile, blades made of ABS material.
- » Air outlet louver made of aluminum profile, blades made of ABS material.
- » Protection of air handling unit installed outdoor against meteorological conditions (precipitation, sand).

Specification

- » Max air face velocity: 5m/s.
- » Working conditions: -40 ÷ +70°C.



CONTROLS

All controls for VENTUS air handling units is available as optional equipment.

Range of controls is always fitted to configuration of the AHU selected in the CCOL4 tool. Controls is capable to regulate all user parameters: air temperature, its humidity, maximum permissible CO₂ concentration and the flow rate. Also, controls support preventive and securing functions like protection of the water heater against freezing or energy recovery system against icing, protection of motors against overloading, monitoring of air filters actual status of contamination and many other. Applied algorithms can optimize performance of all air treatment components in order to minimize consumption of all energy media supplied to the unit.

The system includes control and power supply circuit.



USER



HMI Basic

- » Engaging and disengaging the AHU, change of operational modes.
- » Change of temperature, airflow, humidity, max CO₂ level settings, etc.
- » Errors reporting.
- » Time schedule setting.



HMI Advanced

- » All users and service functions except visualization
 - AHU engaging and disengaging,
 - Change of operational modes.
- » Change of temperature, airflow, humidity, max CO₂ level settings, etc.
- » Parameters setting and reporting.
- » Errors reporting.
- » Time schedule setting.



BMS

- » User function like in HMI Advanced.
- » User's customized visualization (BMS).



Remote visualization

- » All user function like in HMI Advanced:
 - VTS visualization.
- » Clear interface of schedule programming, presenting unit's operating time individually for each day of the week.
- » Energy consumption analysing module.
- » Individual parameters monitoring of each functional block.
- » Filing of all AHU's parameters recorded in few minutes intervals.





PAREMETERS REGULATION FUNCTIONS

Regulation of temperature and humidity


- » Regulation of supply, return air temperature and humidity in handled spaces.
- » Control of water coils valves (heater, cooler) and condensing unit.
- » Control of rotary heat wheel revolutions, by-pass damper and mixing box, depending on AHU type and configuration.

Airflow rate regulation

- » Constant Air Volume (CAV) available as standard.
- » Constant static pressure maintenance in trunk duct (Variable Air Volume – VAV) available as option.
- » Setting of constant revolutions for each fan individually – VFD setting for AC motors or constant revolutions percentage in case of EC motors.

CO₂ regulation

- » By means of mixing box – for units with air recirculation.
- » By means of airflow rate change – for all types of supply and exhaust units (function can be engaged together with mixing box control).



PROTECTION FUNCTIONS

- » Protection against rotary heat wheel icing, by means of wheel revolutions reduction.
- » Protection against hexagonal counterflow and cross-flow recuperator icing by means of by-pass damper opening. Functions realized as optional:
 - Optimizing of icing protection function by change of minimum return air temperature threshold downstream the energy recovery unit vs return air parameters.
 - Minimizing of recovery efficiency drop during defrosting
- » Anti-freezing protection of water heater
 - Antifreeze thermostat installed downstream the heater
 - Strap-on return water temperature sensor
- » Fans overload protection (functions realized by EC motors drives)
- » Fire alarm input – AHU immediate disengaging in case of lack of external start permission from overall fire protection system.



PREVENTIVE FUNCTIONS

- » Constant filter contamination status control:
 - Constant monitoring of filter pressure drop by means of static pressure transducers,
 - Evaluation of filter contamination status for vs actual airflow rate.
- » Fans shutting-down delay – fan's run out for systems with electric heater
- » Water heater pre-heating before fan's start up.
- » Periodical heater pump engaging in summer – to prevent against limescale accumulation
- » Opening of water heater regulation valve before engaging the fans.


TIME SCHEDULE FUNCTIONS

- » Weekly schedule operational modes programming (HMI Advanced i Basic).
- » Clear visualization of schedule settings by means of web-browser (computers and mobile devices).

POWER SUPPLY AND CONTROL CIRCUITS

- » The main component of the controls is the control box – with microprocessor controller installed inside. The control box is usually mounted on side wall of the AHU or in units direct vicinity.
- » Control box is equipped with controller, power protection circuits, terminal block enabling connecting of all control elements.
- » Electric protection of fans, rotary heat wheel drive, control elements and heater pump are installed inside the control box.
- » Control of fan-sets (variable frequency drives in case of AC motors of specialized drives for EC ones) is realized by means of digital communication based on ModBUS protocol. Fan control elements are set with individual address enabling them to be properly identified in the control system.
- » Communication with static pressure and CO₂ transducers also realized by ModBUS protocol.
- » For other control elements, digital or analogue signals are used.







CONTROL ELEMENTS

CONTROL ELEMENTS



Functions and application

- » Regulation of supply and exhaust air temperature.
- » Protection of the energy recovery unit against freezing.
- » Outdoor air temperature measurement in order to identify need of heat/chill recovery and engagement protecting function for water heater.

Operational parameters

- » Measurement range: -50°C to +90°C.
- » Measurement accuracy: $\pm 0,5K$.
- » Sensor type: NTC 10k.
- » Air humidity range: 5 ÷ 100%.
- » Protection degree: IP67.
- » Shielded cable length: max. 100 m.

ROOM AIR TEMPERATURE SENSOR



Functions and application

- » Regulation of temperature in handled space.

Operational parameters

- » Measurement range: -20°C to +70°C.
- » Measurement accuracy: $\pm 0,5K$.
- » Sensor type: NTC 10k.
- » Air humidity range: 5 ÷ 95% no condensation.
- » Protection degree: IP20.
- » Shielded cable length: max. 100 m.

STRAP-ON MEDIUM TEMPERATURE SENSOR



Functions and application

- » Protection of water heater against freezing by means of return medium temperature monitoring.

(Function supported by controller. Sensor out of VTS offer.)

Operational parameters

- » Measurement range: -20°C to +70°C.
- » Measurement accuracy: $\pm 0,5K$.
- » Sensor type: NTC 10k.
- » Air humidity range: 5 ÷ 100%.
- » Protection degree: IP67.
- » Shielded cable length: max. 100 m.

ANTI-FREEZE THERMOSTATE



Functions and application

- » Protection of water heater against freezing by means of air off-coil temperature monitoring (recommended temperature threshold setting: +5°C).

Operational parameters

- » Measurement range: -18 ÷ +15°C.
- » Hysteresis: 1,7 ÷ 12K.
- » Nominal voltage: 30V DC or 230V AC.
- » Output signal: potential-free contact.
- » Protection degree: IP 44.



OVERHEAT PROTECTION THERMOSTATE FOR ELECTRIC HEATER



Functions and application

- » Protection of electric heater against overheating.

Operational parameters

- » Power cut-off temperature setpoint: 65°C.
- » Power re-switch on temperature setpoint : 45°C.
- » Nominal voltage: 20V DC or 230V AC.
- » Output signal: potential-free contact.

DIFFERENTIAL PRESSURE SWITCH



Functions and application

- » Monitoring of filter's contamination.
- » Control of the operation of a direct driven fan unit in case of cooperation with electric heater.

Operational parameters

- » Measurement range: 30 do 500 Pa.
- » Nominal operating voltage: 250V AC (Imax=3A).
- » Output signal: potential free contact.
- » Working temperature range: -20°C do 60°C.
- » Protection degree: IP 54.

FILTER CONTAMINATION INDICATOR



Functions and application

- » Measurement of air pressure drop on filters, activated manually (button).
- » Signal light (LED) informing about exceeding pressure drop thresholds.
- » Low battery warning light signal.

Operational parameters

- » Max. Pressure difference: 800 Pa.
- » Accuracy: 2,5% of the range.
- » Protection degree (interface side): IP 65.

DIFFERENTIAL PRESSURE TRANSDUCER



Functions and application

- » Regulation of supply and exhaust air (CAV function).
- » Regulation of static pressure in ventilation system trunk duct (VAV function).
- » Constant monitoring of filter pressure drop (control of filter contamination level).

Operational parameters

- » Measurement range: 6000 Pa.
- » Measurement accuracy: 0,25% of the range.
- » Communication: ModBus RTU.
- » Supply voltage: 21,5V to 30V DC or 21,5V do 26,5V AC.
- » Working temperature range: -20°C do 50°C.
- » Protection degree: IP 65.



AIR HUMIDITY TRANSDUCER



Functions and application

- » Regulation of supply and return air humidity in handled spaces (support for air humidifying and dehumidifying).
- » Measurement of return air humidity – automatic change of anti-freeze threshold temperature setting of cross-flow recuperator depending on return air parameters*.

Operational parameters

- » Measurement range: 0-100%.
- » Tolerance: +/- 3%.
- » Communication: ModBus RTU.
- » Supply voltage: 24V DC.
- » Working temperature: -40°C to 80°C.
- » Protection degree: IP 65.

* Also available as integrated with air temperature sensor

CO₂ TRANSDUCER



Functions and application

- » Regulation of CO₂ concentration in handled spaces (control of mixing box or airflow rate).

Operational parameters

- » Measurement range: 0 do 2000 ppm.
- » Tolerance:
 - between 400 and 1250 ppm: +/-3%,
 - between 1250 and 2000 ppm: +/-5%.
- » Communication: ModBus RTU.
- » Supply voltage: 24V DC.
- » Working temperature: 0 do 50°C.
- » Protection degree: IP 54.

ON/OFF DAMPER ACTUATOR



Functions and application

- » Airflow opening or closing in the AHU (connectors of air intake and discharge) – for units with water heater actuators with return spring are applied.

Operational parameters

- » Regulation mode: ON/OFF (two-point).
- » Angle of rotation: 90°.
- » Torque: 16 Nm (max damper cross-section: 4 m²).
- » Full open/close time: 120 s (with spring: 10 s).
- » Supply voltage: 24V AC/DC.
- » Working temperature: -20°C do 50°C.
- » Protection degree: IP 54.

SMOOTH CONTROL DAMPER ACTUATOR



Functions and application

- » Smooth regulation of return and fresh air mixing (recirculation) – for units with water heater actuators with return spring are applied.
- » Protection of cross-plate or hexagonal recuperator against frosting – smooth regulation of bypass damper opening.

Operational parameters

- » Regulation mode: 0 do 100% (smooth).
- » Control signal: 0-10V.
- » Angle de rotation: 90°.
- » Torque: 16 Nm (max damper cross-section: 4 m²).
- » Full open/close time: 90s (with spring: 10 s).
- » Supply voltage: 24V AC/DC.
- » Working temperature: -20°C do 50°C.
- » Protection degree: IP 54.



THREE-WAY VALVE FOR WATER HEATER OR COOLER



Functions and application

- » Smooth regulation of water heater or cooler capacity.

Operational parameters

- » Regulation mode: 0 to 100% (smooth).
- » Control signal: 0-10V.
- » Full open/close time: 90 s.
- » Valve supply voltage: 24V AC/DC.
- » Working temperature: +5°C to 50°C.
- » Medium temperature range: -10°C to 120°C.
- » Max glycol concentration: 50%.
- » Protection degree: IP 54.

ELECTRIC HEATER CONTROL MODULE – MHE TYPE



Functions and application

- » Power supply, protection and smooth regulation of electric (heating) capacity of multi-stage electric heaters by means of PWM (Pulse Width Modulation).

Operational parameters

- » Regulation mode: 0 to 100% (smooth).
- » Nominal voltage: 3*400V/50Hz.
- » Control circuits supply voltage: 24V AC.
- » Binary input signal: 3 x 24V DC.
- » Binary output signal 6 x 24V DC.
- » PWM 1 x 24V DC.
- » Working temperature: 0°C to 50°C.

VARIABLE FREQUENCY DRIVE



Functions and application

- » Smooth regulation of fan-set capacity.
- » "Soft-start" of the fan without mechanical and electric shock.
- » Motor protection against overloading and stalling.

Operational parameters

- » Frequency regulation range: 10 ÷ 100 Hz.
- » Communication: ModBus RTU RS485.
- » Supply voltage:
 - single-phase 200 ÷ 240V AC,
 - three-phase 380 ÷ 480V AC.
- » Working temperature: 0°C to 40°C.
- » Protection degree: IP 20.



HMI BASIC USER INTERFACE



Functions and application

- » Maintenance of Air handling unit – temperatures setting and reading, change of operating modes, independent time schedule management, alarm codes displaying.
- » Configuration of controller's universal inputs and outputs.

Operational parameters

- » Power supply directly from the controller.
- » Communication with controller – RS485 serial port.
- » Max length of communication cable: max. 500 m.
- » Working temperature: -20°C to 60°C.
- » Humidity: <85% (no condensation).
- » Protection degree: IP 31.

HMI ADVANCED USER INTERFACE



Functions and application

- » Maintenance of Air handling Unit – parameters setting and reading (temperature, airflow, CO₂, humidity etc), change of operational modes.
- » Weekly schedule programming.
- » Service maintenance – configuration of all advanced AHU operating parameters, configuration controllers universal inputs and outputs.
- » Remote configuring of variable frequency drives.
- » AHU alarms and errors monitoring (full text description) and cancelling.

Operational parameters

- » Power supply directly from the controller
- » Communication with controller – RS485 serial port
- » Max length of communication cable: max. 1200 m,
- » Working temperature: -20°C to 60°C.
- » Humidity: <85% (no condensation).
- » Protection degree: IP 31.

SUPPLY AND CONTROL BOX



Functions and application

- » Control of all components and processes of Air Handling Unit, especially realization of regulation (temperature, airflow, CO₂, humidity) and protection functions (anti-freezing of energy recovery heat exchanger or water heater, fan-sets overloading etc).
- » Alarms handling, self-diagnostics.
- » Filling of all operating parameters history.
- » Communication with user interfaces (HMI).

Operational parameters

- » Supply voltage: 3x400 VAC or 1x230 V AC.
- » Supply frequency: 50 Hz, +/- 1 Hz.
- » Control circuits supply voltage: 24 V AC.
- » Water heater pump supply voltage: 230 V AC (max.10A).
- » Communication with internal controls circuits, VFD's or EC motors controller: ModBus RTU.
- » ModBus communication: TCP/IP.
- » Working temperature: 0 to 50°C.
- » Humidity: <85% (no condensation).
- » Protection degree: IP 54.

VTs

24.2°

30.5°



Esc





04

Units
- VENTUS S-type



ventus

S-TYPE

TECHNICAL SPECIFICATIONS

CASING


- 40 mm "Sandwich" double skin panels made of rigid polyurethane foam
- Inspection panels mounted on AHU side
- High anticorrosive protection:
 - Galvanized zinc (Zn) coating: 180g/m²
 - External protection coating material thickness: polyester / 25µm
- Inspection panels on both sides

AIR FILTERS

- Pleated filtration fabric shielded by steel net, installed in 50 mm thick frame
- Filtration fabric made of polyester fibres
- Working max parameters: max temperature (+70)°C, max. RH100%
- ISO Coarse 75% (ISO 16890) - G4 (EN779)

COOLING COIL

- Hydronic coils - 4, 6 rows available
- DX - 6 rows, 2 sections available
- Max operating pressure - 1,6 MPa
- Testing pressure - 2,1 MPa
- Drain tray: stainless steel, water outlet 1"



DIRECT DRIVE PLUG FAN SET > BLOWER

- Single inlet, radial, backward curved, free running fan
- Direct drive – fan impeller installed directly on motor shaft
- Fan section consisting of single or twin fans
- Smooth regulation

DIRECT DRIVE PLUG FAN SET > AC MOTORS

- Fan and motor mounted on common housing, separated from AHU casing by set of rubber vibration absorbing mounts
- Motors of TEFS (Totally Enclosed, Fan-Cooled)
- Variable Frequency Drive (VFD) – standard part of the fan-set
- Available Energy classes: IE2
- Junction box on casing

DIRECT DRIVE PLUG FAN SET > EC MOTORS

- Set of fan and motor mounted on common rail, fixed to the AHU fan diaphragm.
- EC motors are Permanent Magnet motor, characterised by much higher efficiency vs traditional inductive AC motors.
- Required regulation with 0-10V regulator or ModBus signal
- Junction box on casing

TYPICAL APPLICATION



residential
buildings



industrial
buildings



small
businesses



sports
facilities



retail and
warehouses



garages
and workshops

UNIT CASING:

Monocoque technology - a self supporting shell structure used in Formula 1 car and aviation. This is exactly how we design our products, therefore our units feature low weight and optimal height, are easy for transportation and further installation. Moreover double skin "sandwich" panels with 40 mm rigid polyurethane foam ensure best thermal insulation.

- » Thermal conductivity: PPU $\lambda = 0,022 \text{ W/mK}$
- » PPU density: $\rho = 42 \text{ kg/m}^3$.
- » Casing heat transfer coefficient: $K = 0.6 \text{ W/m}^2\text{K}$
- » Casing mechanical strength:
 $+2500 \text{ Pa} \div 2500 \text{ Pa} < 2 \text{ mm}$
- » Casing tightness: $-400 \text{ Pa} - 0.05 \text{ l/sm}^2$
 $+700 \text{ Pa} - 0.13 \text{ l/sm}^3$
- » Anticorrosive protection:
- Galvanized zinc (Zn) coating: 180 g/m^2
- » External protection coating material thickness:
polyester $25 \mu\text{m}$
- » Inspection panels mounted on AHU side.

NO THERMAL BRIDGES

Our Monocoque casing is a framework free construction. This eliminates the problem of water condensation on the external AHU side - and therefore - no more of harmful water dripping from the ceiling.

DRAIN TRAY

They are fabricated from heavy stainless steel and are to prevent condensation.

COOLING COILS

Fabricated from copper tubes mechanically bonded with aluminum fins and are leak tested at 305 psig pressure.

Hydronic

- » Copper pipe: dimensions: $\frac{1}{2}"$
- » Fin Type: corrugated fin
- » Row: 4 or 6 rows
- » Max operating pressure: 1,6 MPa
- » Testing pressure: 2,1 MPa
- » Equipped with air discharge valve and water outlet valve

> DX

- » Copper pipe: dimensions: $\frac{1}{2}"$
- » Fin Type: corrugated fin
- » Row: 6 rows, 2 - sections
- » Max operating pressure: 1,6 MPa
- » Testing pressure: 2,1 MPa

DIRECT DRIVE PLUG FAN SET

Blower

- » Single inlet, radial, backward curved, free running fan.
- » Impeller made of SAN (styrene/ acrylonitrile) construction material with 20% glass fiber.
- » Direct drive – fan impeller installed directly on motor shaft.
- » Fan section consisting of single or twin fans .

AC Motors

- » Fan and motor mounted on common housing, separated from AHU casing by set of rubber vibration absorbing mounts.
- » Motors of TEFS (Totally Enclosed, Fan-Cooled).
- » Motors fitted for IEC standard.
- » Variable Frequency Drive (VFD) – standard part of the fan-set.
- » Available Energy classes: IE2
- » Available voltage: 1x230V/50Hz, 3x380V/50Hz, 3x400V/50Hz, 3x400V/60Hz.
- » Number of poles: 2.
- » Motor winding insulation class: F (fitted for VFD operations).
- » Bearings lifetime: $L_{10} = 20000 \text{ h} / L_{50} = 100000 \text{ h}$.
- » Protection degree: IP55.
- » Working conditions: 60°C .

EC Motors


- » Set of fan and motor mounted on common rail, fixed to the AHU fan diaphragm.
- » EC motors are Permanent Magnet motor, characterised by much higher efficiency vs traditional inductive AC motors.
- » EC motors (Electronically Commutated) – where mechanical commutator switching the windings has been replaced with electronic one.
- » Change of revolutions is done by means of changing the frequency rate of windings switching (rate or magnetic field rotating).
- » Highly inductive permanent magnets have applied in EC motors used by VTS, which enabled to achieve high torque at relatively small dimensions.
- » Rated voltage: EC motors of nominal capacity equal or less 0,75kW - 1x230V AC.
- » Motor winding insulation class: F.
- » Protection degree: IP54. » Maximum working ambient temperature: 55°C .
- » Lifespan: - 70 000 hours at load not exceeding 70% of nominal capacity at ambient temperature not exceeding 35°C , - 30 000 hours at 100% capacity load at ambient temperature not exceeding 55°C .

AIR FILTERS


- » All Units are provided with air filters.
- » Pleated filtration fabric shielded by steel net, installed in 50 mm thick frame.
- » Filtration fabric made of polyester fibres.
- » Working max parameters: max. temperature $(+70^\circ\text{C})$, max RH100%.
- » ISO Coarse 75% (ISO 16890) - G4 (EN779).

ELECTRICAL WIRING DIAGRAMS


3 phase with VFD



1 phase - 1 EC MOTOR




1 phase - 2 EC MOTOR






Unit size	Fan set with AC Motor									
	Model	Rated Output	Poles	Efficiency Class	Protection Grade	Rated Current at				
						415V/3ph/50Hz	230V/1ph/50Hz	380V/3ph/50Hz	400V/3ph/50Hz	400V/3ph/60Hz
	[-]	[kW]	[-]	[-]	[-]	[A]	[A]	[A]	[A]	[A]
SVS-35	VS 315	1,5	2	IE2	IP55 / F	3,1	5,54	3,36	3,1	3,19
SVS-50	VS 355	1,5	2	IE2	IP55 / F	3,1	5,54	3,36	3,1	3,19
SVS-70	VS 315 x 2	1,5 x 2	2	IE2	IP55 / F	6,2	11,08	6,72	6,2	6,38
SVS-85	VS 400 x 2	1,5 x 2	2	IE2	IP55 / F	6,2	11,08	6,72	6,2	6,38
SVS-100	VS 400 x 2	1,5 x 2	2	IE2	IP55 / F	6,2	11,08	6,72	6,2	6,38

Unit size	Fan set with EC Motor			
	Model	Rated Output	Protection Grade	Rated Current at 230V/1ph/50Hz
	[-]	[kW]	[-]	[A]
SVS-35	VS 315	0,75	IP54 / F	3,7
SVS-50	VS 315	0,75	IP54 / F	3,7
SVS-70	VS 315 x 2	0,75 x 2	IP54 / F	7,2
SVS-85	VS 315 x 2	0,75 x 2	IP54 / F	7,2
SVS-100	VS 315 x 2	0,75 x 2	IP54 / F	7,2



 **100%**
units
factory tested



Unit size	Dimensions			Duct Connection	FAN	Motor	Weight
	H	W	L	h x w	Model	Rated Output	
	[mm]				[-]	[kW]	
SVS-35	530	1130	1120	210 x 700	VS 315	1,5	106
SVS-50	595	1300	1120	310x550	VS 355	1,5	124
SVS-70	530	2000	1120	310x1200	VS 315 x 2	1,5 x 2	181
SVS-85	655	2000	1120	410x1400	VS 400 x 2	1,5 x 2	205
SVS-100	655	2200	1120	410x1400	VS 400 x 2	1,5 x 2	220

Unit size	Min Air Flow		Max Air Flow		Air Flow						
	CMH	CFM	CMH	CFM	CFM						
					0	1000	2000	3000	4000	5000	6000
SVS-35	1500	883	3500	2060							
SVS-50	2100	1236	4500	2660							
SVS-70	3000	1766	7000	4120							
SVS-85	3400	2001	8500	5003							
SVS-100	4200	2472	9500	5621							

Unit size	Coil Volume			Coil Connections			
	WCL4R	WCL6R	DX6R	WCL4R, WCL6R		DX6R	
	[Liters]			ϕD_{in}	ϕD_{out}	ϕD_{in}	ϕD_{out}
SVS-35	6,33	9,5	9,5	DN32	DN32	2x5/8"	2xØ28
SVS-50	8,24	12,36	12,36	DN50	DN50	2xØ22	2xØ35
SVS-70	12,08	18,13	18,13	DN50	DN50	2xØ22	2xØ35
SVS-85	15,44	23,16	23,16	DN50	DN50	2xØ22	2xØ35
SVS-100	17,23	25,84	25,84	DN50	DN50	2xØ22	2xØ42





05

Fan Coil Unit



Technical Specifications

CASING

Top cover material:

- Galvanized steel
- Thickness: 0.8 mm

Base material:

- Galvanized steel
- Thickness: 0.8 mm

Side panel material:

- Galvanized steel
- Thickness: 0.8 mm

Back cover:

- Galvanized steel
- Thickness: 0.8 mm

Top cover for plenum:

- Galvanized steel
- Thickness: 0.8 mm

Side panel for plenum:

- Galvanized steel
- Thickness: 0.8 mm

Plenum box insulation:

- 6 mm closed cell foam


COOLING COIL

Copper pipe:

- Dimensions: 3/8" (9.52 mm)

Fin:

- Thickness: 0.105 mm
- Fin pitch: 10 FPI
- Louvered type Al-fin



BLOWER:

Blower material:

- Type: DIDW Forward Curved Centrifugal Fan
- Material: Galvanized steel

Motor:

- Type: Single phase capacitor type
- Insulation: B
- Protection grade: IP20

FILTER:

- Filter frame: Aluminum alloy
- Material: Double layer aluminum
- Thickness: 12.5 mm
- EU-2 filter grade as per EN779

DRAIN TRAY:

- Material: galvanised steel
- Thickness: 0.8 mm
- Insulation material: PE, 3 mm
- Water outlet: 7/8"
- Powder coated to RAL 9002



Typical applications:



Offices



Hotels




Hospitals



Malls



Technical Specifications

**Unit Casing:**


Galvanized steel casing of minimum 0.8 mm thickness. Casing is internally lined with 6mm closed cell elastomeric foam insulation.

**Drain Tray:**

They are fabricated from heavy gauge galvanized steel and are insulated to prevent condensation. Powder coated on both sides to RAL 9002.

**Cooling Coils:**

Fabricated from copper tubes mechanically bonded with aluminum fins and are leak tested at 350 Psig nitrogen pressure.

**Blower:**

Fans are forward curved centrifugal type of double inlet, statically and dynamically balanced to ensure quiet operation.

**Air Filters:**

All Units are provided with 12.5 mm Aluminum Mesh filter as a standard option. Filters accessible from rear end of the unit and is easily removable by pulling out from unit frame.

**Fan Motors:**

Motors are single phase, 3 speed, 220-240V/1 Phase/50 Hz with internal thermal protection. EC motors available as an option.

**Options:**

Double skin fan coil units with casing made of 0.8mm galvanized steel sheet and 10mm close cell insulation. Decorative fan coil units, suitable for wall or ceiling mounting.





06

WING air curtain



WING C

MAX. AIR RANGE:

4 m

EXHAUST FLOW RATE:

1950-4600 m³/h



DIMENSIONS


200 W/E/C



150 W/E/C



100 W/E/C




Dedicated brackets* and fixing points enable immediate installation of the curtain.

* in offer

STREAM RANGE


Vertical air stream range

(maximum installation height)




Horizontal air stream range

(for vertical installation)



INSTALLATION

Dedicated brackets and fixing points enable immediate installation of the curtain.




DEDICATED BRACKETS




FASTENING PINS


The maximum mounting height is 4m.
The minimum distance between the air outlet of the curtain and the ceiling is only 30 cm.



HORIZONTAL INSTALLATION



VERTICAL INSTALLATION



CONTROL



Controller WING EC

VTS product number	1-4-0101-0451	
Motor support	EC	
Power supply voltage	V/ph/Hz	~230/1/50
Permissible load	A	1A for 230VAC 0,02A for 0-10V
Setting range	°C	5...40
Protection rating	IP	30



Wall controller WING/VOLCANO

VTS product number	1-4-0101-0438	
Motor support	AC	
Power supply voltage	V/ph/Hz	~230/1/50
Permissible load	A	6(3)
Settings range	°C	10...30
Protection rating	IP	30



Potentiometer EC (0-10 V)

VTS product number	1-4-0101-0453	
Power supply voltage	V/ph/Hz	~230/1/50
Permissible load	A	0,02 A for 0-10V
Work mode	-	Manual
Protection rating	IP	30



Door sensor (reed switch)*

VTS product number	1-4-0101-0454	
Contact configuration	NO	
Switching current	500 mA	
Switching voltage	max 200 V	
Connection	screw	


* cooperation with controller WING EC

ALL EC AIR CURTAINS ARE CHARACTERIZED BY EASE AND SIMPLICITY OF CONNECTION



ELECTRICITY SAVINGS

Modern design of the EC motor and fan saves energy compared to old generation solutions.



SIMPLE CLEANING

Thanks to the optimized construction of the covers, cleaning the curtain is comfortable and does not require the disassembly of any part, always ensuring hygienic operation.



GALVANIZED STEEL CASING

Double coating (galvanization + powder paint) provides long-term protection against corrosion and consistent aesthetic qualities. Casing colour RAL 9016.



SMART DOOR PROTECTION

Air curtain with advanced WING EC CONTROLLER may perform according to the door opening sensor. Smart Door protection gives you not only permanent temperature comfort but also secure inside environment from dust, pollution, insects and unpleasant scents.

TECHNICAL PARAMETERS

Parameters	Unit	AMBIENT CURTAIN					
		WING C100		WING C150		WING C200	
		AC	EC	AC	EC	AC	EC
VTS item No.		1-4-2801-0041	1-4-2801-0061	1-4-2801-0042	1-4-2801-0062	1-4-2801-0043	1-4-2801-0063
maximum door width (1 device)	m	1		1,5		2	
maximum door height (vertical stream range)*	m	4					
maximum exhaust flow rate	m³/h	1950		3200		4600	
supply voltage	V/ph/Hz	~230/1/50					
motor power	kW	0,235	0,2	0,375	0,3	0,58	0,45
rated current	A	1,2	1,1	1,7	1,3	2,6	1,9
weight	kg	20,5	19	27,5	25,5	34,5	32,5
protection rating	IP	20					
max. velocity*	m/s	11					
casing colour	RAL	RAL 9016, outlet grid: RAL 9022					

WING C100, C150, C200 [AMBIENT CURTAIN]

Fan speed	WING C100			WING C150			WING C200		
	I	II	III	I	II	III	I	II	III
Qp [m³/h]	1050	1500	1950	1500	2250	3200	2340	3400	4600
db (A) **	53	59	62	54	62	63	57	61	63



* air stream range depends on curtain operation speed


** measurement conditions: semi-open space, horizontal installation on the wall, measurement performed 5m away from the device



NOTES

[illegible]

PSYCHROMETRIC CHART





VTSGROUP Clima Gulf FZCO.

P.O.BOX #18061,
Plot No. S20126
Hebel Ali Freezone, Dubai - U.A.E
tel: +971 (4) 881 1945
fax: +971 (4) 889 4998
e-mail: dubai@vtsgroup.com

VTSGROUP Clima LLC - Abu Dhabi Branch

P.O.Box # 36060
2nd Floor , Office # 3A
Sh. Saeed Al Nahyan Building
Al Falah Street, Abu Dhabi-U.A.E
Tel. + 971 (02) 6276101
Fax + 971 (02) 6276121
e-mail: abudhabi@vtsgroup.com

VTSGROUP Clima Oman

Technical Trading Company LLC.
(Al-Sulaimi Group Holding)
PO Box 1693, PC 112, Ruwi
Muscat - Oman
tel: +968 24 70 35 15

VTSGROUP Clima Kuwait

PO Box 24354
Safat 13104, Kuwait
tel: +965 22401320
fax: +965 22404527

VTSGROUP Clima KSA

A.A Turki Corporation LLC - ATCO Bldg.
280 Istanbul Street, Exit 18, Sulai
PO Box 8077 Riyadh 11482
Kingdom of Saudi Arabia
tel: +966 11 8100760
mobile: +966 54 536 8818

Due to continuous improvement of the products, VTS reserves right to implement modifications.
Some of technical data and descriptions may vary from the actual products specification.
Before placing the order, please, confirm all technical specification with VTS sales representative.